

COMPANY IDENTITY: ICP INTERNATIONAL, LLC
 PRODUCT IDENTITY: MULTIPURPOSE ATF
 REVISION DATE: 10/15/2007

DATE: 05/1/13
 PAGE 1 OF 5

MATERIAL SAFETY DATA SHEET

THIS MSDS COMPLIES WITH 29 CFR 1910.1200 (HAZARD COMMUNICATION STANDARD)

IMPORTANT: Read this MSDS before handling & disposing of this product.

Pass this information on to employees, customers, & users of this product.

SECTION 1. CHEMICAL PRODUCT & COMPANY IDENTIFICATION / HAZARD RATINGS

PRODUCT IDENTITY: MULTIPURPOSE ATF
 COMPANY IDENTITY: ICP International, LLC
 COMPANY ADDRESS: P.O. BOX 7267
 COMPANY CITY: Cut and Shoot, TX 77306
 COMPANY PHONE: 1-936-494-3013
 CHEMTREC PHONE: 1-800-424-9300

HAZARD RATINGS:
 HEALTH : 1
 FLAMMABILITY : 1
 REACTIVITY : 0

SECTION 2. INGREDIENT & REGULATORY INFORMATION

All components of this product are on the TSCA list.

SARA TITLE III Section 313 Supplier Notification

This product does not contain any toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning & Community Right-to-Know Act of 1986 and of 40 CFR 372. This information must be included in all MSDSs that are copied and distributed for this material.

SARA TITLE III INGREDIENTS	CAS#	WT.% (REG SECTION)	RQ (LBS.)
Hydro treated Light Paraffinic Distillates	64742-55-8	N.A.	None
Ethoxylated long chain Alkylamine		N.A.	None
Diphenylamine	122-39-4	0.01 to 0.09	None
C.I. Solvent red 164		N.A.	None
*Xylene	1330-20-7	<1	100
*Ethylbenzene	100-41-4	<1	1000

SARA SECTION 311 / 312 HAZARDS: Acute Health.

MATERIAL	CAS#	TWA+ (OSHA)	TLV (ACGIH)	HAP
Xylene	1330-20-7	100 ppm	100 ppm	Yes
Ethylbenzene	100-41-4	100 ppm	100 ppm	Yes

All components of this product showing aYes@ under aHAP@ above, using manufacturers= data, based on EPA Method 311 are EPA Hazardous Air Pollutants.

SARA SECTION 313 TOXIC CHEMICAL

Chemical Name	CAS#	Concentration
None		

CERCLA 102 (a)/DOT Hazardous Substances: (+ indicates DOT Hazardous Substance)

Seq	Chemical Name	CAS#	Concentration
01+	Toluene	108-88-3	0.01-0.09
02+	Xylene	1330-20-7	0.00875
03+	Ethyl benzene	100-41-4	0.001675

CERCLA/DOT Hazardous Substances (Sequence numbers and RQ=s):

Seq	RQ
01+	1000
01+	100
02+	1000

DISTRIBUTOR NAME: ICP International, LLC
PRODUCT IDENTITY: MULTIPURPOSE ATF

DATE: 05/1/13
PAGE: 2 of 5

SECTION 2. INGREDIENT & REGULATORY INFORMATION (CONT.)

CALIFORNIA PROPOSITION 65:

The following detectable components of this product are substances, or belong to classes of substances, known to the State of California to cause cancer and/or reproductive toxicity.

Chemical Name	CAS #
TOLUENE	108-88-3

DOT SHIPPING NAME: Not Regulated
DOT DRUM LABEL: None

SECTION 3. HAZARDS IDENTIFICATION

THRESHOLD LIMIT VALUE: Not Known

CONTAINS: Hydro treated Light Paraffinic Distillates,
Ethoxylated long chain Alkylamines, Diphenylamine,
C.I. Solvent Red 164
Xylene
Ethylbenzene

ACUTE HAZARDS

EYE & SKIN CONTACT:

Causes eye irritation. May cause skin irritation.
Avoid contact with eyes, skin, and clothing.

INHALATION:

Not a significant hazard.

SWALLOWING:

May cause irritation to the gastrointestinal tract.

CHRONIC HAZARDS:

None Known.

CONDITIONS AGGRAVATED:

Persons with skin disorders should avoid use.

SECTION 3. HAZARDS IDENTIFICATION (CONTINUED)

CANCER AND REPRODUCTIVE DAMAGE HAZARDS

CANCER AND REPRODUCTIVE DAMAGE HAZARDS:

None Known

SECTION 4. FIRST AID MEASURES AND PROCEDURES

EYE CONTACT:

Flush eyes with large amounts of water for at least 15 minutes, lifting eyelids to insure complete flushing of surface. Get medical attention if irritation develops and persists.

SKIN CONTACT:

Wash skin with soap and water. Remove contaminated clothing. If irritation develops and persists, get medical attention. Launder contaminated clothing before reuse.

INHALATION:

Remove exposed person to fresh air if adverse effects are observed.

SWALLOWING:

Do **NOT** induce vomiting. If conscious, have victim drink 2 or 3 glasses of milk or water. Get immediate medical attention.

NOTE TO PHYSICIAN:

None

SECTION 5. FIRE FIGHTING MEASURES

LOWER FLAMMABLE LIMITS IN AIR (% by vol.):

Not Known

FLASH POINT (TEST METHOD) : COC

>320°F / >160°C

FLAMMABILITY CLASSIFICATION:

CLASS III B

EXTINGUISHING MEDIA:

Use foam, water spray, dry powder, carbon dioxide (CO₂). Water can be used to cool and protect exposed material.

SPECIAL FIRE FIGHTING PROCEDURES:

Approach fire from upwind side. Avoid breathing smoke, fumes, mist, or vapors on downwind side. Do not enter fire area without full bunker equipment, including NIOSH Approved Positive Pressure Breathing Equipment.

UNUSUAL EXPLOSION AND FIRE PROCEDURES:

Toxic fumes, gases or vapor may evolve on burning.
Containers may rupture from internal pressure if confined to fire area. Cool with water.
Get nonessential personnel out of area.

SECTION 6. ACCIDENTAL RELEASE MEASURES

SPILL OR LEAK PROCEDURES:

Personal Protective Equipment must be worn (SEE SECTION 8). Ventilate area if spilled in confined space or other poorly ventilated area.
Dike to contain spill. Pick up free liquid for recycle and/or disposal. Residual liquid and/or solid can be absorbed on inert material. Keep from sewers and natural waterways.

WASTE DISPOSAL METHOD:

Not considered a hazardous waste when uncontaminated.
Dispose of according to local, state, and federal regulations.

HANDLING:

Keep away from heat and flame.
Use with adequate ventilation.
Avoid breathing vapor.
Do not get in eyes, on skin, or on clothing.
Wash thoroughly after handling.
Empty container contains product residue which may exhibit hazards of product. Do not flame cut, braze, or weld near full or empty container.
Odorous and toxic fumes may form from the decomposition of this product if stored at temperatures in excess of 113°F/45°C for extended periods of time or if heat sources in excess of 250°F/121°C are used.

STORAGE:

Store in a cool ventilated area below 140°F/60°C.
Keep container closed.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS:

Use NIOSH approved respirator or mask to prevent overexposure.
Avoid prolonged or repeated breathing of vapors.
Use self-contained breathing apparatus for entry into confined space, for other poorly ventilated areas, and for large spill clean-up sites.

VENTILATION:

Use local exhaust and general mechanical ventilation.

PERSONAL PROTECTIONS:

Avoid contact with eyes. Wear face shield, safety glasses, or goggles.
Avoid prolonged or repeated contact with skin. Wear chemically resistant gloves and long sleeved shirt to prevent contact.

SECTION 9. PHYSICAL DATA

APPEARANCE:	RED LIQUID
ODOR:	MILD ADDITIVE
BOILING RANGE:	Not Determined
GRAVITY @ 60°F:	
SPECIFIC GRAVITY (Water = 1):	.866
POUNDS/GALLON:	7.216
VOC=S (VAPOR PRESSURE >0.44 LBS./SQ. IN) (LBS./GAL):	0.0
TOTAL VOLATILE ORGANIC COMPOUNDS (TVOC) (g/L):	0.0
NONEXEMPT VOLATILE COMPOUNDS (CVOC):	0.0
VAPOR PRESSURE (mm of Hg) @ 20°C:	Not Determined
VAPOR DENSITY (air = 1):	Not Determined
WATER ABSORPTION:	Negligible
% VOLATILE BY VOL.:	0.0

SECTION 10. REACTIVITY DATA

STABILITY:

Stable.

CONDITIONS TO AVOID:

Keep away from heat and open flames.

MATERIALS TO AVOID:

Keep away from Oxidizers.

HAZARDOUS DECOMPOSITION PRODUCT:

Smoke, toxic fumes, Carbon Dioxide and Carbon Monoxide under fire conditions.

HAZARDOUS POLYMERIZATION:

Cannot occur.

NOTICE

The supplier disclaims all expressed or implied warranties of fitness or merchantability for a specific use, with respect to the product, or the information provided herein, except for conformation to contracted specifications. All information appearing herein is based upon data obtained from manufacturer and/or recognized technical sources. While the information is believed to be accurate, we make no representations as to its accuracy or sufficiency.

Conditions of use are beyond our control, and therefore users are responsible for verifying the data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling, and disposal of the product. Users also assume all risks in regards to the publication or use of, or reliance upon, information contained herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or process.