

MATERIAL DATA SAFETY SHEET

DOT 3 BRAKE FLUID

SECTION 1: IDENTIFICATION

PRODUCT IDENTITY: DOT 3 BRAKE FLUID
CHEMICAL FAMILY: Brake Fluid
CAS NUMBER: Mixture
CHEMICAL NAME: Mixture
SYNONYMS: Mixture of glycol ethers; Polyglycols; Glycols

Supplier

ICP International, LLC
P.O Box 7267
Cut and Shoot, Texas 77306
24 Hour Emergency Contact
CHEMTREC 800-424-9300

Business Contact

Customer Service
1-936-494-3013

SECTION 2: HAZARD IDENTIFICATION

Emergency Overview

This material is HAZARDOUS by OSHA Hazard Communication definition.

Signal Word

WARNING

Hazards

Liquid, vapors or mist may be irritating to eyes, skin and respiratory tract.

NFPA®

| | |
|--------------|---|
| Health | 1 |
| Flammability | 1 |
| Reactivity | 0 |

HMIS®

| | |
|--------------|---|
| Health | 2 |
| Flammability | 1 |
| Reactivity | 0 |

Physical State

Liquid

Color

Clear to Amber

Odor

Mild Odor

Odor Threshold

No Value Available

Potential Health Effects

Routes of Exposure

Skin, Eye, Inhalation

Signs and Symptoms of Acute Exposure

See component summary.

- Triethylene Glycol Monobutyl Ether 143-22-6
Contact may cause severe eye irritation, but not expected to cause permanent damage. No other signs or symptoms of acute exposure are expected during normal use with standard manufacturing practices.
- Triethylene Glycol Monomethyl Ether 112-35-6
Mildly toxic by ingestion and skin contact. A mild skin and eye irritant.
- Diethylene Glycol 111-46-6
This substance may cause effects on the central nervous system, liver and kidneys.
- Tetraethylene Glycol Monobutyl Ether 1559-34-8
No known chronic health effects.
- Tetraethylene Glycol 112-60-7
No adverse chronic human health effects have been reported for this material.
- Triethylene Glycol Monoethyl Ether 112-50-3
May be irritation to the skin.
- Pentaethylene Glycol Monobutyl Ether 23601-39-0
Not expected to present a significant acute health hazard with short term exposure
- Diethylene Glycol Monobutyl Ether 112-34-5
Moderate eye irritant. Effects of eye irritation are reversible. Contact may cause mild skin irritation. Not expected to be a sensitizer. Not a skin absorption hazard.
- Polyethylene Glycol Methyl Ether 9004-74-4
Mild skin irritant. May cause minor eye irritation.
- Diethylene Glycol Monoethyl Ether 111-90-0
Moderate eye irritant. Slight skin irritant. May produce symptoms of CNS depression including headache, dizziness, nausea, loss of sense of balance, drowsiness, and visual disturbances.

Skin

May cause slight irritation if left in contact with skin. May be absorbed in toxic amounts through the skin.

Inhalation

Due to low vapor pressure, significant exposure by inhalation appears unlikely. However, exposure to high concentrations of mist, aerosol, or vapors at elevated temperatures may cause irritation, coughing, and discomfort in the nose, throat and chest

Eye

Can cause irritation and moderate conjunctivitis following contact.

Ingestion

May produce symptoms of CNS depression including headache, dizziness, nausea, loss of sense of balance, drowsiness, and visual disturbances.

Chronic Health Effects

See component summary.

- Triethylene Glycol Monobutyl Ether 143-22-6
Repeated or prolonged contact may cause skin irritation. May cause dermatitis by defatting the skin from prolonged or repeated contact.
- Triethylene Glycol Monomethyl Ether 112-35-6
No chronic health hazards are expected to occur from anticipated conditions of normal use of this material.
- Polyethylene Glycol Methyl Ether 9004-74-4
No known chronic health effects.
- Diethylene Glycol 111-46-6
No adverse chronic human health effects have been reported for this material.
- Tetraethylene Glycol 112-60-7
No adverse chronic human health effects have been reported for this material.
- Tetraethylene Glycol Monobutyl Ether 1559-34-8
No adverse chronic human health effects have been reported for this material.
- Triethylene Glycol Monoethyl Ether 112-50-3
No known chronic health effects
- Pentaethylene Glycol Monobutyl Ether 23601-39-0
No known chronic health effects
- Diethylene Glycol Monobutyl Ether 112-34-5
May cause dermatitis by defatting the skin from prolonged or repeated contact.
- Polyethylene Glycol Methyl Ether 9004-74-4
No known chronic health effects
- Diethylene Glycol Monoethyl Ether 111-90-0
Repeated or prolonged skin contact may cause slight transient irritation. Skin absorption may add significantly to the overall toxic effect. Prolonged or high exposures may cause CNS effects and liver and kidney changes.

Conditions Aggravated by Exposure

Any pre-existing disorders or diseases of the eyes, skin, blood, and/or central nervous system (CNS)

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

| Component Name | CAS# | EU Inventory | Conc. Wt. % | Risk | Symbol |
|--------------------------------------|------------|--------------|-------------|------|--------|
| Triethylene Glycol Monobutyl Ether | 143-22-6 | 205-592-6 | 23 <= 35 | None | None |
| Triethylene Glycol Monomethyl Ether | 112-35-6 | 203-962-1 | 3 <= 10 | None | None |
| Diethylene Glycol | 111-46-6 | 203-872-2 | 10 <=20 | R22 | Xn |
| Tetraethylene Glycol Monobutyl Ether | 1559-34-8 | 216-322-1 | 9 <=14 | None | None |
| Tetraethylene Glycol | 112-60-7 | 203-989-9 | 6 <=10 | None | None |
| Triethylene Glycol Monoethyl Ether | 112-50-5 | 203-978-9 | 8 <=20 | None | None |
| Pentaethylene Glycol Monobutyl Ether | 23601-39-0 | 245-774-2 | 2 <=5 | None | None |
| Diethylene Glycol Monobutyl Ether | 112-34-5 | 203-961-6 | 1 <=8 | R36 | Xi |
| Polyethylene Glycol Methyl Ether | 9004-74-4 | Not Assigned | <= 4.0 | None | None |
| Diethylene Glycol Monoethyl Ether | 111-90-0 | 203-919-7 | <= 2.0 | None | None |

Concentrations given are typical values
See section 16 for full text of risk phrases

SECTION 4: FIRST AID MEASURES

General

Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid. For specific information refer to the Emergency Overview in Section 3 of this MSDS.

Skin

Wash skin with soap and water. Remove contaminated clothing. Launder contaminated clothing before reuse.(Discard contaminated shoes.) If irritation occurs get medical attention.

Inhalation

Remove exposed person to fresh air. If breathing is difficult, give oxygen. If breathing has stopped, give artificial respiration. CALL A PHYSICIAN IMMEDIATELY.

Eye

Flush eyes with large amounts of water for at least 15 minutes, lifting eyelids to insure complete flushing of surface. GET MEDICAL ATTENTION IMMEDIATELY

Ingestion

Never give anything by mouth to an unconscious person. Have patient drink several glasses of water, then induce vomiting by having patient tickle back of throat with finger. Keep airway clear. GET MEDICAL ATTENTION IMMEDIATELY.

SECTION 5: FIRE FIGHTING MEASURES

Flammable Properties

Classification

OSHA/NFPA Class IIIB combustible liquid

Flash Point:

121 ° C (249 ° F) PMCC

Auto Ignition Temperature

310 ° C (590 ° F)

Lower Flammable Limit

No Data Available

Upper Flammable Limit

No Data Available

Extinguishing Media

Suitable: SMALL FIRE: Use dry chemicals, CO², water spray or alcohol resistant foam. LARGE FIRE: Use water spray, water fog or alcohol resistant foam.

Unsuitable: Do not use solid water stream.

Protection of Firefighters

Protective Equipment/Clothing: Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters protective clothing will only provide limited protection.

Fire Fighting Guidance: Fight fire from maximum distance or use unmanned hose handlers or monitor nozzles. Move containers from fire area if you can do it without risk. Cool containers with flooding quantities of water until well after fire is out. Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank. Always stay away from tanks engulfed in fire.

Hazardous Combustion Products: Carbon Oxides (CO, CO²)

SECTION 6: ACCIDENTAL RELEASE MEASURES

Release Response

Combustible liquid. Eliminate all sources of ignition. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Use clean non-sparking tools to collect absorbed material.

SECTION 7: HANDLING AND STORAGE

Handling

Normal precautions common to good manufacturing practice should be followed in handling and storage. Open and handle container with care. Do not handle near heat, sparks or flame. Avoid contact with incompatible agents. Use only with adequate ventilation/personal protection. Avoid contact with eyes, skin, and clothing. Do not enter storage area unless adequately ventilated. Metal containers involved in the transfer of this material should be grounded and bonded. Handle empty containers with care as residue may be combustible. After handling, always wash hands thoroughly with soap and water. Isolate, vent, drain, wash and purge systems or equipment before maintenance or repair. Observe precautions pertaining to confined space entry. Check atmosphere for explosiveness and oxygen deficiencies. Use only non-sparking tools.

Storage

Store in well ventilated area. Store away from heat, open flame and strong oxidizing agents. Keep container tightly closed and properly labeled. Ground all equipment containing this material. Use only non-sparking tools.

SECTION 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Engineering Controls

Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits.

Personal Protection

Inhalation A respiratory protection program that meets OSHA's 29 CFR 1910.134 or ANSI Z88.2 requirements must be followed whenever workplace conditions warrant respirator use. No occupational exposure limit(s) have been established for this material or its components. If nuisance mists cause discomfort, U.S. National Institute for Occupational Safety and Health (NIOSH) approved respiratory protection is suggested.

Skin Wear chemical resistant gloves such as rubber, neoprene, or vinyl. When skin contact is possible, protective clothing including gloves, apron, sleeves, boots, head and face protection should be worn. The equipment must be cleaned thoroughly after each use.

Eye Safety glasses are required as minimum requirements. Use splash goggles when eye contact due to splashing or spraying liquid is possible.

Additional Remarks

Selection of appropriate personal protective equipment should be based on an evaluation of the performance characteristics of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet facilities. Promptly remove soiled clothing and wash thoroughly before reuse. Use care in walking on spilled material. Material spilled on hard surfaces can be a serious slipping/falling hazard.

Occupational Exposure Limits

| Component Name | Source / Date | Value | Type | Notation |
|-----------------------|----------------------|--------------|-------------|-----------------|
| Tetraethylene Glycol | US (ACGIH) / 2007 | N/L | | |
| | US (OSHA) / 2007 | N/L | | |

| | | |
|------------------------------------|-------------------|-----|
| Diethylene Glycol | US (ACGIH) / 2006 | N/L |
| | US (OSHA) / 1993 | N/L |
| Triethylene Glycol Monoethyl Ether | US (ACGIH) / 2003 | N/L |
| | US (OSHA) / 2003 | N/L |
| Diethylene Glycol Monobutyl Ether | US (ACGIH) / 2004 | N/L |
| | US (OSHA) / 2000 | N/L |
| Diethylene Glycol Monoethyl Ether | ACGIH / 2006 | N/L |

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Liquid. Amber.

Odor: Mild Odor.

Odor Threshold: No value available.

pH: Not applicable

Boiling Point/Boiling Range: >218 ° C (> 425 ° F) @ 760 mm Hg

Freezing Point/ Melting Point: -50 ° C (-58 ° F)

Flash Point: 121 ° C (249.8 ° F) PMCC

Auto-Ignition: 310 ° C (590 ° F)

Flammability: OSHA/NFPA Class IIIB combustible liquid.

Lower Flammable Limit: No Data Available.

Upper Flammable Limit: No Data Available.

Explosive Properties: No Data Available.

Page 7 of 19

Oxidizing Properties: No Data Available.

Vapor Pressure: No Data Available.

Evaporation Rate: No Data Available.

Relative Density: 1.05

Viscosity: No Data Available.

Solubility (Water): Soluble in water.

Partition Coefficient (KOW): No Data Available.

Additional Physical and Chemical Properties: No Additional Information Available.

SECTION 10: STABILITY AND REACTIVITY

Chemical Stability

This product is stable.

Conditions to Avoid

Avoid contact with strong oxidizers, excessive heat, sparks or open flame.

Substances to Avoid

Oxidizers

Decomposition Products

Carbon oxides (CO, CO²)

Hazardous Polymerization

Will Not Occur.

Reactions with Air and Water

Does not react with air, water or other common materials.

SECTION 11: TOXICOLOGICAL INFORMATION

PRODUCT INFORMATION

Product Summary

This substance appears to be of low toxicity, except for possible mild irritant effects in humans. A high dose may produce central nervous system depression, but there are no reports of adverse health effects from occupational exposure.

Page 8 of 19

COMPONENT INFORMATION

- Triethylene Glycol Monobutyl Ether 143-22-6

Acute Toxicity – Lethal Doses

LD50 (Oral) Rat 5300 MG/KG

LD50 (Skin) Rabbit 3540 UL/KG

Irritation

Skin Repeated or prolonged contact may cause slight skin irritation. No significant signs or symptoms indicative of any health hazard are expected to occur as a result of skin absorption exposure. Not expected to be a sensitizer.

Eye Contact may cause severe eye irritation, but is not expected to cause permanent damage.

Target Organ Effects

Eye. Skin.

Repeated Dose Toxicity

No known chronic health effects. Repeated or prolonged contact with skin may cause defatting and drying of the skin which may result in dermatitis.

Reproductive Effects

Not expected to occur.

Developmental Effects

Results from animal studies demonstrate that this material is not a teratogen, nor is it toxic to the developing embryo or fetus at non-maternally toxic doses.

Carcinogenicity

Not listed by IARC, NTP, or OSHA.

- Triethylene Glycol Monomethyl Ether 112-35-6

Acute Toxicity – Lethal Doses

LD50 (Oral) Rat 11.8 G/KG

LD50 (Skin) Rabbit 7.4 G/KG

Irritation

Skin This substance is a mild skin irritant.

Eye This product is suspected to be a mild eye irritant.

Repeated Dose Toxicity

In severe overexposure enough material might be absorbed into the skin to cause systemic injury.

Reproductive Effects

Laboratory tests indicate high doses may cause adverse reproductive effects in rats and mice.

Carcinogenicity

No conclusive data found in literature search. Not listed by IARC, NTP, or OSHA.

- Polyethylene Glycol Methyl Ether 9004-74-4

Acute Toxicity – Lethal Doses

LD50 (Oral) Rat 22 - 40 G/KG

LD50 (Skin) Rabbit > 20 ML/KG

Reproductive Effects

Maternally toxic oral doses did not produce malformations and was not selectively toxic to developing conceptus.

- Diethylene Glycol 111-46-6

Acute Toxicity – Lethal Doses

LD50 (Oral) Rat 12,565 MG/KG BWT

Mouse 23,700 MG/KG BWT

LD50 (Skin) Rabbit 11,900 MG/KG

Acute Toxicity – Effects

Inhalation None Expected

Irritation

Skin Slight skin irritant. Not expected to be a sensitizer.

Eye May cause minor eye irritation.

Repeated Dose Toxicity

Diethylene glycol given to rats in the diet for two years caused bladder stones, tumors, and kidney and liver damage. These effects were probably due to contaminating ethylene glycol, and the bladder stones were formed from oxalate crystals.

Reproductive Effects

Reproductive and developmental effects have been noted in animals following very large (>3000 mg/kg bw/day) oral doses. However, comparable internal dose levels are not possible with dermal or inhalation exposures under normal conditions of use. Therefore, Diethylene glycol is not considered a possible reproductive or developmental hazard except during very large oral doses.

Carcinogenicity

Not listed by IARC, NTP, or OSHA. No evidence for carcinogenicity was found with a chronic skin-painting study in mice. No carcinogenic or tumor promoting effects in rats exposed up to 2.5% solutions in drinking water for 108 weeks. Older feed studies utilizing limited number tissues but very high doses also provide no evidence of carcinogenicity. Therefore, this substance should not be considered a concern for carcinogenicity.

- Triethylene Glycol Monobutyl Ether 143-22-6

Acute Toxicity – Lethal Doses

LD50 (Oral) Rat 5300 MG/KG

LD50 (Skin) Rabbit 3540 UL/KG

Irritation

Skin Repeated or prolonged contact may cause slight skin irritation. No significant signs or symptoms indicative of any health hazard are expected to occur as a result of skin absorption exposure. Not expected to be a sensitizer.

Eye Contact may cause severe eye irritation, but not expected to cause permanent damage.

Target Organ Effects

Eye. Skin.

Repeated Dose Toxicity

No known chronic health effects. Repeated or prolonged contact with skin may cause defatting and drying of the skin which may result in dermatitis.

Reproductive Effects

Not expected to occur.

Developmental Effects

Results from animal studies demonstrate that this material is not a teratogen, nor is it toxic to the developing embryo or fetus at non-maternally toxic doses.

Carcinogenicity

Not listed by IARC, NTP, or OSHA.

- Tetraethylene Glycol 112-60-7

Acute Toxicity – Lethal Doses

LD50 (Oral) Rat > 18,056 MG/KG

LD50 (Skin) Rabbit > 20000 MG/KG

Carcinogenicity

Not listed by IARC, NTP, or OSHA.

- Polyethylene Glycol 25322-68-3

Acute Toxicity – Lethal Doses

LD50 (Oral) Rat > 30000 MG/KG

LD50 (Skin) Rabbit > 20000 MG/KG

Carcinogenicity

Not listed by IARC, NTP, or OSHA.

- Tetraethylene Glycol Monobutyl Ether 1559-34-8

Repeated Dose Toxicity

No known chronic health effects.

Carcinogenicity

Not listed by IARC, NTP, or OSHA.

- Pentaethylene Glycol Monobutyl Ether 23601-39-0

Repeated Dose Toxicity

No known chronic health effects.

Carcinogenicity

Not listed by IARC, NTP, or OSHA.

- Diethylene Glycol Monobutyl Ether 112-34-5

Acute Toxicity – Lethal Doses

| | | |
|--------------------|-------|------------|
| <u>LD50 (Oral)</u> | Rat | 5080 MG/KG |
| | Mouse | 2406 MG/KG |

| | | |
|--------------------|--------|------------|
| <u>LD50 (Skin)</u> | Rabbit | 2764 MG/KG |
|--------------------|--------|------------|

Irritation

Skin This substance is a mild skin irritant

Eye Moderate eye irritant

Target Organ Effects

Eye

Reproductive Effects

In vivo animal studies show no adverse reproductive effects.

Developmental Effects

Results from animal studies demonstrate that this material is not a teratogen or toxic to the developing embryo or fetus.

Genetic Toxicity

Negative for genotoxicity both in vitro in vivo tests.

Carcinogenicity

Not listed by IARC, NTP, or OSHA.

- Diethylene Glycol Monoethyl Ether 111-90-0

Acute Toxicity – Lethal Doses

| | | |
|--------------------|-----|------------|
| <u>LD50 (Oral)</u> | Rat | 5400 MG/KG |
|--------------------|-----|------------|

| | | |
|--------------------|--------|----------|
| <u>LD50 (Skin)</u> | Rabbit | 9.0 G/KG |
|--------------------|--------|----------|

Irritation

Skin Slight skin irritant

Eye Moderate eye irritant

Repeated Dose Toxicity

In a two year drinking water study with rats and mice, no adverse effects were observed at 1% and 5%, respectively.

Carcinogenicity

Not listed by IARC, NTP, or OSHA.

SECTION 12: ECOLOGICAL INFORMATION

PRODUCT INFORMATION

Ecotoxicity

This material is highly soluble in water. Laboratory toxicity tests indicate that it is not significantly toxic to fish and aquatic invertebrates, although amphibians may be more sensitive. Wildlife species may be more susceptible since mammals and birds do not readily metabolize this material. The odor and flavor of this material may attract some wildlife and cause them to consume spilled material.

Environmental Fate and Pathway

This material will biodegrade rather rapidly in both soil and water, and will not persist in the environment. Due care should be taken to avoid accidental releases to aquatic or terrestrial systems.

Persistence and Degradability

Bioaccumulation: This material is highly soluble in water and should not bioaccumulate in aquatic or terrestrial organisms.

COMPONENT INFORMATION

- Triethylene Glycol Monobutyl Ether 143-22-6

Ecotoxicity

No Data Available

Page 13 of 19

Environmental Fate and Pathway

Expected to have high mobility in soils. It is water soluble and is expected to have low volatility. If released to the atmosphere, this material should exist in both the vapor and particulate phases. Vapor phase is degraded in the atmosphere by reaction with photochemically produced hydroxyl radicals. Particulate phase of this material may be physically removed from air by wet and dry deposition.

- Triethylene Glycol Monomethyl Ether 112-35-6

Ecotoxicity

This material is highly soluble in water. Limited toxicity tests indicate this material should exhibit low toxicity to aquatic organisms. The odor and flavor of this material may attract some wildlife and cause them to consume spilled material.

Environmental Fate and Pathway

This material will biodegrade rather rapidly in both soil and water, and will not persist in the environment. Due care should be taken to avoid accidental releases to aquatic or terrestrial systems.

Persistence and Degradability

Bioaccumulation: Because of this materials high solubility and rapid biodegradability, it is unlikely that bioaccumulation will occur in aquatic or terrestrial systems. Models estimate that this material will preferentially partition to water versus air or soil.

- Diethylene Glycol 111-46-6

Ecotoxicity

Diethylene glycol (DEG) is highly soluble in water. Laboratory tests indicate that DEG is not significantly toxic to fish or aquatic invertebrates. While there is no wildlife toxicity data available on DEG, laboratory tests on rats would indicate that it should not be highly toxic to mammals.

Environmental Fate and Pathway

This material is volatile and water soluble. It is not expected to absorb onto soils or sediments. Expected to have high mobility in soils. This material is expected to exist solely as a vapor in the ambient atmosphere. Vapor-phase is degraded in the atmosphere by reaction with photochemically produced hydroxyl radicals. The particulate phase of this material may be physically removed from the air by wet and dry deposition. This material is not expected to persist in the environment.

Persistence and Degradability

Stability in water: Diethylene glycol (DEG) is highly soluble in water.

Biodegradation: This material is expected to be readily biodegradable.

Bioaccumulation: $BCF < 1.0$ This material is not expected to bioaccumulate.

Persistence and Degradability

Stability in soil: The KOC value suggests that this compound would be highly mobile if released onto the soil and would not absorb to suspended solids or sediments.

Biodegradation: This material is expected to be partially or slowly biodegradable.

Bioaccumulation: $BCF < 1.0$ This material is not expected to bioaccumulate.

- Tetraethylene Glycol Monobutyl Ether 1559-34-8

Ecotoxicity

No data available.

Environmental Fate and Pathway

No data available.

- Tetraethylene Glycol 112-60-7

Ecotoxicity

This material is highly soluble in water. Limited toxicity tests indicate this material should exhibit low toxicity to aquatic organisms. The odor and flavor of this material may attract some wildlife and cause them to consume spilled material.

Acute Toxicity to Fish

LC50/96 HOURS > 1000 mg/l

Acute Toxicity to Aquatic Invertebrates

EC50/48 HOURS Daphnia magna. > 1000 mg/l

Toxicity to Aquatic Plants

EC50/96 HOURS Green Algae (Selenastrum) > 1000 mg/l

Toxicity to Microorganisms

EC50/6 HOURS Bacteria > 100 mg/l

Environmental Fate and Pathway

No data available.

Other Adverse Effects

No data available.

- Triethylene Glycol Monoethyl Ether 112.50-5

Ecotoxicity

No data available.

Environmental Fate and Pathway

Expected to have high mobility in soils. Volatilization from dry soil surfaces is expected. Volatilization from moist soil surfaces is expected. This material is expected to exist solely as a vapor in the ambient atmosphere. Vapor phase is degraded in the atmosphere by reaction with photochemically produced hydroxyl radical.

Persistence and Degradability

Biodegradation: This material is expected to be readily biodegradable.

Bioaccumulation: BCF <1.0 This material is not expected to bioaccumulate.

Page 15 of 19

- Pentaethylene Glycol Monobutyl Ether 23601-39-0

Ecotoxicity

No data available.

Environmental Fate and Pathway

No data available.

- Diethylene Glycol Monobutyl Ether 112-34-5

Ecotoxicity

Acute Toxicity to Fish

LC50/96 HOURS silverside minnow. 2,000 mg/l

LC50/96 HOURS bluegill. 1,300 mg/l

Summary: This material is not harmful or toxic to fish.

Acute Toxicity to Aquatic Invertebrates

Summary: No data available.

Acute Toxicity to Aquatic Plants

Summary: No data available.

Environmental Fate and Pathway

Expected to have high mobility in soils. It is water soluble and is expected to have low volatility. This material is expected to exist solely as a vapor in the ambient atmosphere. Vapor phase is degraded in the atmosphere by reaction with photochemically produced hydroxyl radicals. Hydrolysis is not expected to be an important factor in the environmental fate process for this material.

Persistence and Degradability

Stability in Soil: The Koc value suggests that this compound would be highly mobile if released onto the soil and would not absorb to suspended solids or sediments.

Biodegradation: This material is expected to be readily biodegradable.

Bioaccumulation: $2.0 \text{ BCF} < 5$ This material is not expected to bioaccumulate.

- Polyethylene Glycol Methyl Ether 9004-74-4

Ecotoxicity

No data available.

Environmental Fate and Pathway

No data available.

Page 16 of 19

- Diethylene Glycol Monoethyl Ether 111-90-0

Ecotoxicity

This material is expected to have low toxicity to aquatic species. However, due caution should be exercised to prevent the accidental release of this material to the environment.

Acute Toxicity to Fish

LC50/24 HOURS goldfish > 5000 mg/l

LC50/96 HOURS fathead minnow. 26,500 mg/l

Environmental Fate and Pathway

Expected to have high mobility in soils. Volatilization from dry soil surfaces is expected. While this material may evaporate into the air from dry soil, it is unlikely to evaporate from moist soil or water. This material is expected to exist solely as a vapor in the ambient atmosphere. The vapor phase of this material is degraded in the atmosphere by reaction with photochemically produced hydroxyl radicals and ozone.

Persistence and Degradability

Biodegradation: Incubation of Diethylene glycol monoethyl ether for 5, 10, and 20 days without an acclimation period resulted in theoretical BOD values of 5, 31, and 48% respectively. This material is expected to be readily biodegradable.

Bioaccumulation: BCF = 0.2 This material is not expected to bioaccumulate.

SECTION 13: DISPOSAL CONSIDERATIONS

Dispose of all waste and contaminated equipment in accordance with all applicable federal, state and local health and environmental regulations. Recovery and reuse, rather than disposal, should be the ultimate goal of handling efforts. The materials resulting from clean-up operations may be hazardous wastes and therefore, subject to specific regulations.

SECTION 14: TRANSPORT INFORMATION

Special Requirements

If you reformulate or further process this material, you should consider re-evaluation of the regulatory status of the components listed in the compositions section of this sheet, based on the final composition of your product

Proper Shipping Name BRAKE FLUID, OTHER THAN PETROLEUM

SECTION 15: REGULATORY INFORMATION

Regulatory Status

| Country | Inventory | | |
|----------------|-----------|---|--|
| Australia | AICS | X | |
| Canada | DSL | | |
| Canada | NDSL | | X = All components are included or are otherwise |
| China | IECS | | Exempt from inclusion on this inventory |
| European Union | EINECS | | |
| European Union | ELINCS | | |
| European Union | NLP | | |
| Japan | ENCS | | |
| Korea | ECL | | |
| Philippines | PICCS | | |
| United States | TSCA | X | |

All components of this product are listed or are exempt from listing on the TSCA 8(b) inventory. If identified components of this product are listed under the TSCA 12(b) Export Notification rule, they will be listed below.

SARA 311/312

Based on available information, this material is classified as the following health and/or physical hazards according to Section 311 & 312.

Immediate Acute Health Hazard
Delayed (Chronic) Health Hazard
Fire Hazard

SARA 313

This material contains the following chemicals with known CAS numbers subject to the reporting requirements of SARA Title III, Section 313 and 40 CFR 372:

| <u>Component</u> | <u>Reporting Threshold</u> |
|--|----------------------------|
| Diethylene Glycol Monobutyl Ether / CAS # 112-34-5 | 1.0% |
| Triethylene Glycol Monobutyl Ether / CAS # 143-22-6 | 1.0% |
| Diethylene Glycol Monoethyl Ether / CAS # 111-90-0 | 1.0% |
| Triethylene Glycol Monoethyl Ether / CAS # 112-50-5 | 1.0% |
| Triethylene Glycol Monomethyl Ether / CAS # 112-35-6 | 1.0% |

Page 18 of 19

SECTION 16: OTHER INFORMATION

DATE: 11/19/96 REVISED 9/28/07, 16 SECTION FORMAT

All Relevant Risk Phrases

None
R22 – Harmful if swallowed
R36 – Irritating to eyes

DISCLAIMER OF RESPONSIBILITY

The supplier disclaims all expressed or implied warranties of fitness or merchantability for a specific use, with respect to the product, or the information provided herein, except for conformation to contracted specifications. All information appearing herein is based upon data obtained from manufacturer and/or recognized technical sources. While the information is believed to be accurate, we make no representations as to its accuracy or sufficiency.

Conditions of use are beyond our control, and therefore users are responsible for verifying the data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all

risks of their use, handling, and disposal of the product. Users also assume all risks in regards to the publication or use of, or reliance upon, information contained herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or process.