

COMPANY IDENTITY: ICP INTERNATIONAL, LLC  
PRODUCT IDENTITY: POWER STEERING FLUID

DATE: 05/01/13  
PAGE 1 OF 5  
REVISION DATE: 0801501

### MATERIAL SAFETY DATA SHEET

THIS MSDS COMPLIES WITH 29 CFR 1910.1200 (HAZARD COMMUNICATION STANDARD)  
IMPORTANT: Read this MSDS before handling & disposing of this product.  
Pass this information on to employees, customers, & users of this product.

#### SECTION 1. CHEMICAL PRODUCT & COMPANY IDENTIFICATION / HAZARD RATINGS

|  |                  |
|--|------------------|
| PRODUCT IDENTITY: POWER STEERING FLUID   |                  |
| COMPANY IDENTITY: ICP INTERNATIONAL, LLC | HAZARD RATINGS:  |
| COMPANY ADDRESS: P.O. BOX 7267           | HEALTH : 1       |
| COMPANY CITY: CUT AND SHOOT, TX 77306    | FLAMMABILITY : 1 |
| COMPANY PHONE: 1-936-494-3013            | REACTIVITY : 0   |
| CHEMTREC PHONE: 1-800-424-9300           |                  |

#### SECTION 2. INGREDIENT & REGULATORY INFORMATION

All components of this product are on the TSCA list.

SARA TITLE III Section 313 Supplier Notification

This product does not contain any toxic chemical subject to reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and of 40 CFR 372. This information must be included in all MSDSs that are copied and distributed for this material.

| SARA TITLE III INGREDIENTS                  | CAS#       | WT.% (REG SECTION) | R.Q. (LBS.) |
|---|------------|--------------------|-------------|
| Solvent Refined Light Paraffinic Distillate | 64741-89-5 | N.A.               | None        |
| Solvent Refined Heavy Paraffinic Distillate | 64741-88-4 | N.A.               | None        |
| Zinc C1-C14 Alkyldithiophosphate            | 68649-42-3 | 0.1 (313 as Zinc)  | None        |

| MATERIAL                                    | CAS#       | TWA+ (OSHA) | TLV (ACGIH) | HAP |
|---|------------|-------------|-------------|-----|
| Solvent Refined Light Paraffinic Distillate | 64741-89-5 | 5 mg/m3     | 5 mg/m3     | No  |
| Solvent Refined Heavy Paraffinic Distillate | 64741-88-4 | 5mg/m3      | 5mg/m3      | No  |

No components of this product are EPA Hazardous Air Pollutants (HAP).

DISTRIBUTOR NAME: ICP INTERNATIONAL, LLC  
PRODUCT IDENTITY: POWER STEERING FLUID

DATE: 05/01/13  
PAGE: 2 of 5  
REVISION DATE: 02/17/2003

## **SECTION 2. INGREDIENT & REGULATORY INFORMATION (CONT.)**

### **CALIFORNIA PROPOSITION 65:**

This product does not contain any known chemical known to the State of California to cause cancer or reproductive damage.

DOT SHIPPING NAME: Not Regulated

DOT DRUM LABEL: None

## **SECTION 3. HAZARDS IDENTIFICATION**

THRESHOLD LIMIT VALUE: Not Known

CONTAINS: Refined Light & Heavy paraffinic Distillates,  
Zinc C1-C14 Alkyldithiophosphate,  
Hydroxyalkyl Carboxylic Ester

### **ACUTE HAZARDS**

#### **EYE & SKIN CONTACT:**

Causes eye irritation. May cause skin irritation.  
Avoid contact with eyes, skin, and clothing.

#### **INHALATION:**

This product is not a significant inhalation hazard.

#### **SWALLOWING:**

This product can be a major irritation to the gastrointestinal tract.

#### **CHRONIC HAZARDS:**

None Known.

#### **CONDITIONS AGGRAVATED:**

Persons with skin disorders should avoid use.

DISTRIBUTOR NAME: ICP INTERNATIONAL, LLC  
PRODUCT IDENTITY: POWER STEERING FLUID

DATE: 05/01/13  
PAGE: 3 OF 5  
REVISION DATE: 02/17/2003

### **SECTION 3. HAZARDS IDENTIFICATION (CONTINUED)**

#### **CANCER AND REPRODUCTIVE DAMAGE HAZARDS**

CANCER AND REPRODUCTIVE DAMAGE HAZARDS:

None Known

### **SECTION 4. FIRST AID MEASURES AND PROCEDURES**

#### **EYE CONTACT:**

Flush eyes immediately with large amounts of water for at least 15 minutes, lifting eyelids to insure complete flushing of surface. Get medical attention if irritation develops and persists.

#### **SKIN CONTACT:**

As a precaution, wash skin thoroughly with soap and water. Remove contaminated clothing. If irritation develops and persists, get medical attention. Launder contaminated clothing before reuse.

#### **INHALATION:**

Remove exposed person to fresh air if adverse effects are observed.

#### **SWALLOWING:**

Do NOT induce vomiting. If conscious, have victim drink 2 or 3 glasses of water. Get immediate medical attention.

#### **NOTE TO PHYSICIAN:**

Treat symptomatically.

### **SECTION 5. FIRE FIGHTING MEASURES**

LOWER FLAMMABLE LIMITS IN AIR ( % by vol.):

Not Determined

FLASH POINT (TEST METHOD) : COC

>300°F / >154°C

FLAMMABILITY CLASSIFICATION:

CLASS III B

#### **EXTINGUISHING MEDIA:**

Use foam, dry powder, carbon dioxide (CO<sub>2</sub>). Water can be used to cool and protect exposed material.

#### **SPECIAL FIRE FIGHTING PROCEDURES:**

Approach fire from upwind side. Avoid breathing smoke, fumes, mist, or vapors on downwind side. Do not enter fire area without full bunker equipment, including NIOSH Approved Positive Pressure Breathing Equipment.

#### **UNUSUAL EXPLOSION AND FIRE PROCEDURES:**

Toxic fumes, gases or vapor may evolve on burning.  
Containers may rupture from internal pressure if confined to fire area. Cool with water.  
Get nonessential personnel out of area.

## **SECTION 6. ACCIDENTAL RELEASE MEASURES**

### **SPILL OR LEAK PROCEDURES:**

Personal Protective Equipment must be worn, ( See Section 8). Ventilate area if spilled in confined space or other poorly ventilated area. Dike to contain spill. Pick up free liquid for recycle and/or disposal. Residual liquid and/or solid can be absorbed on inert material. Keep from sewers and natural waterways.

### **WASTE DISPOSAL METHOD:**

Not considered a hazardous waste when uncontaminated.  
Waste management should be in compliance with local, state, and federal regulations.

## **SECTION 7. HANDLING AND STORAGE**

### **HANDLING:**

Keep away from heat and flame.  
Use with adequate ventilation.  
Avoid breathing vapor.  
Do not get in eyes, on skin, or on clothing.  
Wash thoroughly after handling.  
Empty container contains product residue which may exhibit hazards of product.  
Do not flame cut, braze, or weld near full or empty container.  
Odorous and toxic fumes may form from the decomposition of this product if stored at temperatures in excess of 113°F/45°C for extended periods of time or if heat sources in excess of 250°F/121°C are used.

### **STORAGE:**

Store in a cool ventilated area below 140°F/60°C.  
Keep container closed.

## **SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

### **EXPOSURE CONTROLS:**

Use NIOSH approved respirator or mask to prevent overexposure.  
Avoid prolonged or repeated breathing of vapors.  
Use self-contained breathing apparatus for entry into confined space, for other poorly ventilated areas, and for large spill clean-up sites.

### **VENTILATION:**

Use local exhaust and general mechanical ventilation.

### **PERSONAL PROTECTIONS:**

Avoid contact with eyes. Wear face shield, safety glasses, or goggles.  
Avoid prolonged or repeated contact with skin. Wear chemically resistant gloves and long sleeved shirt to prevent contact.

DISTRIBUTOR NAME: ICP INTERNATIONAL, LLC  
PRODUCT IDENTITY: POWER STEERING FLUID

DATE: 05/01/13  
PAGE: 5 OF 5  
REVISION DATE: 02/17/2003

### SECTION 9. PHYSICAL DATA

|  |                |
|--|----------------|
| APPEARANCE:  | AMBER LIQUID   |
| ODOR:  | MILD PETROLEUM |
| BOILING RANGE:                                       | Not Determined |
| GRAVITY @ 60°F:                                      |                |
| SPECIFIC GRAVITY (Water = 1):                        | 0.8738         |
| POUNDS/GALLON:                                       | 7.276          |
| VOC=S (VAPOR PRESSURE >0.44 LBS./SQ. IN) (LBS./GAL): | 0.0            |
| TOTAL VOLATILE ORGANIC COMPOUNDS (CVOC) (g/L):       | 0.0            |
| NONEXEMPT VOLATILE COMPOUNDS (CVOC):                 | 0.0            |
| VAPOR PRESSURE (mm of Hg) @ 20°C:                    | <0.01          |
| VAPOR DENSITY (air = 1):                             | Not Determined |
| WATER ABSORPTION:                                    | Negligible     |
| % VOLATILE BY VOL.:                                  | 0.0            |

### SECTION 10. REACTIVITY DATA

#### STABILITY:

Stable.

#### CONDITIONS TO AVOID:

Keep away from heat and open flames.

#### MATERIALS TO AVOID:

Keep away from Oxidizers.

#### HAZARDOUS DECOMPOSITION PRODUCT:

Smoke, Carbon Dioxide and Carbon Monoxide under fire conditions.

#### HAZARDOUS POLYMERIZATION:

Cannot occur.

### NOTICE

The supplier disclaims all expressed or implied warranties of fitness or merchantability for a specific use, with respect to the product, or the information provided herein, except for conformation to contracted specifications. All information appearing herein is based upon data obtained from manufacturer and/or recognized technical sources. While the information is believed to be accurate, we make no representations as to its accuracy or sufficiency.

Conditions of use are beyond our control, and therefore users are responsible for verifying the data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling, and disposal of the product. Users also assume all risks in regards to the publication or use of, or reliance upon, information contained herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or process.